

SELECTLOK®

QLD | NT
Laurel Nilsen
0401 989 235
lnilsen@selectlok.com.au

NSW | ACT
Daniel Korman
0401 989 000
dkorman@selectlok.com.au

VIC | TAS
Justin Newitt
0416 656 695
jnewitt@selectlok.com.au

WA | SA
Andrena Winning
0423 569 543
awinning@selectlok.com.au



NEW PRODUCTS RANGE WINTER 2025

NEW PRODUCTS RANGE WINTER 2025

EVOLUTION & IND-C SERIES SWING HANDLES

EVOLUTION SERIES | SWITCH UP - MODULAR SWING HANDLE



- **Multi-Insert Technology** available in: Pad-lockable, economy key (CL001, 92268, CL604, CL003) & half-euro profile inserts (**Half-euro cylinders sold separately**) *Handle is non-locking without an insert.
- **Modular design** allows for easy conversion between any standard Selectlok S Cutout swing handle (Millennium, Eselon and Evolution Series) and the F Cutout door profile via the patented adapter plate.
- **Polyamide - IP42:** Ideal for indoor or protected applications.
- **Zinc, black PC & chrome PLT - IP66:** Suitable for full outdoor exposure.
- **90° rotation with positive “click” feedback:** Provides clear feedback confirmation and improved stability in use.
- **Short cam-shaft design:** Ideal for tight spaces or when spindle modification is required.
- **Modularity and symmetry:** Engineered for use w/ biaxial symmetrical door frame designs using F Cutout profiles, allows for 180° handle rotation and seamless integration w/ LH or RH door orientations w/o changing enclosure or door designs. Perfect for pairing w/ Selectlok’s advanced F-Series Symmetrical Door Technology (**FSDT**) range.
- **Vandal-resistant, low-profile design.**
- **Helps reduce inventory complexity:** One handle fits many configurations.

PART NO. (Refer to table)

ITEM	PART NO. MATERIAL/FINISH CODE	CUTOUT	LOCK INC	PART NO.
Swing Handle	PBB (Polyamide, black)	S (Adaptive to F)	NO	1107S-EV2-SPBB0
Swing Handle	ZBB (Zinc, black powder-coated)	S (Adaptive to F)	NO	1107S-EV2-SZBB0
Swing Handle	ZCC (Zinc, bright chrome plated)	S (Adaptive to F)	NO	1107S-EV2-SZCC0
Insert: Padlock	SS (Stainless steel, 316)	Not Applicable	N/A	1107S-EV2-SS-INPAD
Insert: CL001	ZB / ZC (Zinc, black PC or chrome PLT)	Not Applicable	YES	1107S-EV2-Z#-IN01
Insert: 92268	ZB / ZC (Zinc, black PC or chrome PLT)	Not Applicable	YES	1107S-EV2-Z#-IN02
Insert: 604	ZB / ZC (Zinc, black PC or chrome PLT)	Not Applicable	YES	1107S-EV2-Z#-IN03
Insert: CL003	ZB / ZC (Zinc, black PC or chrome PLT)	Not Applicable	YES	1107S-EV2-Z#-IN07
Insert: Half-euro	ZB / ZC (Zinc, black PC or chrome PLT)	Not Applicable	NO	1107S-EV2-Z#-INU3

FSDT | F CUTOUT ADAPTER PLATE (F-SERIES, SYMMETRICAL DOOR TECHNOLOGY)



PART NO. 1107S-FCUTOUT-01

- **Modular design:** For converting standard S Cutout handles to suit F Cutout door profiles.
- **Allows 180° (LH/RH) installation** of S Cutout handles into symmetrical doors w/ F Cutout.
- **Superior ingress protection:** F Cutout adapter plate enables retention of both the handle’s and enclosure’s original IP ingress rating (*when used “as-intended”*)
- **Quality materials:** High-quality zinc alloy, zinc plated

EVOLUTION SERIES, ECONOMY BARREL SWING HANDLE

- ▶ **Short cam-shaft design:** Ideal for modern space conscious builds where an 8mm spindle-shafts isn't an option.
- ▶ **Low-profile styling:** Vandal-resistant, flush design suits any enclosure.
- ▶ **Positive tactile feedback:** A positive "click" at 90° confirms full engagement.
- ▶ **Integrated barrels:** Industry ready keys avail. - CL001, 92268, CL604 or CL003
- ▶ **Polyamide - IP42:** Ideal for indoor or protected applications.
- ▶ **Zinc, black PC & chrome PLT - IP66:** Suitable for full outdoor exposure.
- ▶ **F Cutout compatibility:** Allows for easy conversion between any std. Selectlok S Cutout swing handle (Millennium, Eselon and Evolution Series) and the all-new F Cutout door profile via the patented adapter plate.
- ▶ **Modularity and symmetry:** Engineered for use with true biaxial symmetrical frame designs utilising the new F Cutout door profile, allows for 180° handle rotation and seamless integration with either LH or RH door orientations w/o ever needing to change your door or enclosure designs. Perfect for pairing with Selectlok's advanced F-Series Symmetrical Door Technology (**FSDT**) range.



PART NO. (Refer to table)

ITEM	PART NO. MATERIAL/FINISH CODE	CUTOUT	PART NO.
Swing Handle: CL001	PBB (Polyamide, black)	S (Adaptive to F)	1107S-EV1-SPBB-01
Swing Handle: CL001	ZBB / ZCC (Zinc, black PC or chrome PLT)	S (Adaptive to F)	1107S-EV1-SZ##-01
Swing Handle: 92268	ZBB / ZCC (Zinc, black PC or chrome PLT)	S (Adaptive to F)	1107S-EV1-SZ##-02
Swing Handle: 604	ZBB / ZCC (Zinc, black PC or chrome PLT)	S (Adaptive to F)	1107S-EV1-SZ##-03
Swing Handle: CL003	ZBB / ZCC (Zinc, black PC or chrome PLT)	S (Adaptive to F)	1107S-EV1-SZ##-07

IND-C SERIES | IOT ELECTRONIC SWING HANDLE (INTERNET OF THINGS)

SINGLE POINT HANDLE: PART NO. 1107SBBE01-IND-C-001

ROD CONTROL MECHANISM HANDLE: PART NO. 1107SBBE01-IND-C-002

- ▶ **Access method:** Mechanical key + remote control (DO)
- ▶ **Lock status:** Blue and green indicator lights
- ▶ **IP65 ingress rated:** Suitable for outdoor applications
- ▶ **Includes:** 3M loose wiring harness
- ▶ **RC2 pry proof rated**
- ▶ **Power usage:** 12V | Unlock current $\leq 350\text{mA}$, standby current $\leq 50\text{mA}$
- ▶ **Mechanical key backup:** Lockable with cylinder barrel
- ▶ **Keyed alike 001:** Other codes may be available upon request
- ▶ **Cams:** MCAM-## (*Sold separately*)



PADDLE & BRIDGE HANDLES | RING PULL, TOGGLE & PUSH KNOB LATCHES

PADDLE HANDLE WITH INTERNAL EMERGENCY RELEASE

HANDLE: PART NO. PH-001-01

STRIKER / LOCKING BAR: PART NO. PH-001-01-01 (*Sold separately*)

- ▶ **IP66 rated:** Suitable for full outdoor exposure.
- ▶ **Two-step locking for enhanced security:**
Primary click - secures the door,
Secondary click - compresses the gasket.
- ▶ **Internal emergency release tab (RED) for safety:**
Handle can be opened from inside even if the door is locked externally.
- ▶ **Available in:** CH751 and 805 keys
- ▶ **Rear fixing:** Mounting bracket
- ▶ **Materials:** PA6+GF30 & Q235 trivalent chromate zinc plated
- ▶ **Cutout Dimensions:** 112mm (L) x 82mm (H)



PUSH HANDLE KNOB LATCH

PA, CHROME: PART NO. LA-001-01
PA, BLACK: PART NO. LA-001-02

- ▶ IP40 rated
- ▶ Orientation: LH or RH interchangeable
- ▶ Premium design: Slam feature, auto-latching, Steps: Push to close, pull to open, pop-knob to lock

KEY LOCKABLE TOGGLE LATCH - SMALL

PART NO. TOG001-2-1

- ▶ Keyed alike: K080
- ▶ Max. static load: 700Nm
- ▶ Material: Bracket - Stainless steel
Housing & Keeper - Zinc die-cast, black PC
- ▶ Dimensions: 76mm (L) x 32mm (W) x 21mm (H)

TORQUE HINGES

ROTOR-STATOR TORQUE HINGE

BLACK: PART NO. TH2338-4-1
SILVER: PART NO. TH2338-4-2

- ▶ ROM: 270°
- ▶ Life-span: Over 25,000x cycles
- ▶ Fixings: M5 screws (rear fixing)
- ▶ Orientation: LH or RH interchangeable
- ▶ Torque spec: 2Nm symmetric torque (Static: $\pm 20\%$)
- ▶ Material: Rotor-stator/hinge - Zinc die-cast, Pin - Nickel plated steel (stainless steel pin also avail.)
- ▶ Finish: Pocked Silver PLT or black PS (plastic spray)

CAMS & CORNER HINGE

THREE-POINT CAM WITH STOPPER

- ▶ Cam length: 45mm Avail. w/: Raised or normal studs
- ▶ H-Offset: Dist. from door (ext.) to cams contact patch

PART NO. (Refer to table)

H=	STUDS	PART NO.
4mm	Normal (0mm)	TCAM-1-4
26mm	Raised (4mm)	TCAM-2-26
28mm	Raised (4mm)	TCAM-2-28
30mm	Raised (4mm)	TCAM-2-30
32mm	Raised (4mm)	TCAM-2-32

BH SERIES, MODULAR-BRIDGE HANDLE

330MM HANDLE: PART NO. BH-01
430MM HANDLE: PART NO. BH-02



- ▶ Modular handle: Ø30mm tube/pipe (various lengths)
- ▶ Precise and tight fit of pipe into the support bases
- ▶ Mounting: M8 (hex.) nuts/bolts (not supplied)
- ▶ Total assembled length: +64mm to adv. pipe (L=)
- ▶ Suitable for: Either vertical or horizontal applications
- ▶ Included: Ø30mm pipe (L=) and 2x end support base
- ▶ Individual components: *Sold Separately*

FLUSH PULL RING LATCH

PA: PART NO. SEL-MS739-2P-1-7 (Lockable)
PA: PART NO. SEL-MS739-2P-2-7 (Non-locking)
SS: PART NO. SEL-MS739-2S-1-7 (Lockable)
SS: PART NO. SEL-MS739-2S-2-7 (Non-locking)

- ▶ Material: Stainless steel - lock case, stand, handle, core & key
- ▶ Material: Zinc DC - housing, bracket & handle PA - insert
- ▶ P.T. & Cutout: 1-6 | Ø50 (mm)



ROTOR-STATOR TORQUE BUTT-HINGE

40X40: PART NO. THL161-4040-1N-1
50X50: PART NO. THL161-5050-2N-1

- ▶ ROM: 270°
- ▶ Life-span: Over 25,000x cycles
- ▶ Fixings: M5 screws (front fixing)
- ▶ Orientation: LH or RH interchangeable
- ▶ 40x40 torque specification: 1Nm symmetric torque
- ▶ 50x50 torque specification: 2Nm symmetric torque
- ▶ Static torque specification: $\pm 20\%$
- ▶ Material & Finish:
Rotor-stator/hinge - Zinc die-cast, black plastic spray
Pin - Nickel plated steel

HEAVY-DUTY Ø14MM GAS STRUTS

1000Nm: PART NO. G830-14-C19-1000N
1500Nm: PART NO. G830-14-C19-1500N

- ▶ Heavy-duty Ø14mm piston shaft dia.
- ▶ Ends: C19, metal
- ▶ Extended Length: 830mm
- ▶ Stroke: 360mm
- ▶ 1000Nm & 1500Nm: Pressures available off-the-shelf.
 - Can be re-gassed to between 1000Nm ~ 2000Nm (Pressures cannot be decreased, only increased)
 - Unique configurations and pressures may be available subject to MOQ's and leadtimes (Contact us for more)



SELECTLOK AUSTRALIA
+61 (03) 8318 4900
sales@selectlok.com.au
www.selectlok.com.au