

SELECTLOK®



QUICK REFERENCE GUIDE

Switchboard and Enclosure Manufacturers

QLD | NT

Laurel Nilsen
0401 989 235

lnilsen@selectlok.com.au

NSW | ACT

Daniel Korman
0401 989 000

dkorman@selectlok.com.au

VIC | TAS

Justin Newitt
0416 656 695

jnewitt@selectlok.com.au

WA | SA

Andrena Winning
0423 569 543

awinning@selectlok.com.au



PINTLE HINGE
PART NO. (Refer to table)

- ▶ 16mm (H) x 6mm (pin diameter) x varying lengths
- ▶ Interchangeable male & female components
- ▶ Stainless steel pin

MATERIAL	LENGTH (mm)	FINISH	PART NO.	BOX QTY
Brass	50mm	Chrome plated	HIB500-1	200
Stainless steel 316	50mm	Polished	HIB500-1-SS	200
Brass	82mm	Chrome plated	HIB650-1	200
Brass	82mm	Black EDP coated	HIB650-1-BLK	200
Stainless steel 316	82mm	Polished	HIB650-1-SS	200



STEPPED PINTLE HINGE
PART NO. (Refer to table)

- ▶ 6mm (pin diameter)
- ▶ Interchangeable male & female components
- ▶ Stainless steel pin

HEIGHT (FEMALE)	HEIGHT (MALE)	LENGTH	MATERIAL	FINISH	PART NO.	BOX QTY
16mm	19mm	82mm	Brass	Chrome plated	HIB820-1	200
16mm	19mm	82mm	Stainless steel 316	Polished	HIB820-1SS	200
16mm	24mm	82mm	Brass	Chrome plated	HIB880-1	200
16mm	24mm	44mm	Brass	Chrome plated	HIB520-1	200

PINTLE HINGE MOUNTING SCREWS
PART NO. (Refer to table)



- ▶ M6 x 8mm
- ▶ Serrations under head for earthing purposes (hex head)
- ▶ Suits pintle hinges

MATERIAL	HEAD TYPE	FINISH	PART NO.	BOX QTY
Mild steel	Hex multi-head serrated (7mm)	Zinc plated	F-HMHSS-M6X8	100
Stainless steel 304	Hex multi-head serrated (7mm)	-	F-HMHSS-M6X8-SS	100
Mild steel	Large hex multi-head serrated (10mm)	Zinc plated	HIB650-SCREW	100
Stainless steel 316	Large hex multi-head serrated (10mm)	-	HIB650-SCREW-SS	100
Mild steel	Socket head cap (5mm)	Zinc plated	F-SCS-M6X8-ZP	100
Stainless steel 304	Socket head cap (5mm)	-	F-SCS-M6X8-SS	100



60MM SPRING LOADED BUTT HINGE
PART NO. CL253-6
BOX QTY: Sold individually

- ▶ Stainless steel 304
- ▶ For self-closing applications
- ▶ Suitable for LH or RH doors
- ▶ 60mm (L) x 40mm (W) x 1.5mm (T)
- ▶ 5mm (Dia) knuckle



CONCEALED CORNER HINGE
PART NO. PI5346-MB-6-2-S

- ▶ Rear fixing stud
- ▶ Suits door thickness: 1.5~2.3mm
- ▶ Zinc die-cast, black with mild-steel pin
- ▶ 65mm (L) x 20mm (W) x 18mm (D)
- ▶ Pair with **Switch Up** swing handle for use in symmetrical enclosure designs

SWING HANDLES

MILLENNIUM SWING HANDLE, PADLOCKABLE

PART NO. (Refer to table)
BOX QTY: 40



- Shaft: Mild steel, zinc plated
- Hasp: Stainless steel 304
- IP65 rated
- 90° left & right stopper
- Suits padlock up to 13mm

BASE	HANDLE	PART NUMBER
Black EDP coated	Black EDP coated	1107SBB04
Black EDP coated	Chrome plated	1107SBC04
Chrome plated	Chrome plated	1107SCC04

MILLENNIUM SWING HANDLE, PADLOCKABLE (SS)

PART NO. (Refer to table)
BOX QTY: 50



- Shaft & hasp: Stainless steel 316
- IP65 rated
- 90° left & right stopper
- Suits padlock up to 13mm

BASE	HANDLE	PART NUMBER
Mirror-like finish	Mirror-like finish	1107-SS02-316
Brushed	Brushed	1107-SS02-316-B

MILLENNIUM SWING HANDLE, ECONOMY BARREL

PART NO. (Refer to table)
BOX QTY: 40



- Shaft: Mild steel, zinc plated
- IP65 rated, 90° left & right stopper
- Other keys available: 604, 320

BASE / HANDLE FINISH	KEYED	PART NUMBER
Chrome plated	CL001	1107SCCU3-01
Chrome plated	92268	1107SCCU3-02
Chrome plated	CL003	1107SCCU3-07

MILLENNIUM SWING HANDLE, ECONOMY BARREL (SS)

PART NO. (Refer to table)
BOX QTY: 40



- Shaft & hasp: Stainless steel 316
- IP65 rated, 90° left & right stopper
- Other keys available: 604, 320

BASE / HANDLE FINISH	KEYED	PART NUMBER
Mirror-like finish	CL001	1107SSSU3-01D
Mirror-like finish	92268	1107SSSU3-02D
Mirror-like finish	CL003	1107SSSU3-07D

ESELON SWING HANDLE, PADLOCKABLE (ALT)

PART NO. 1107SCCU3N-PAD
BOX QTY: 40



- Zinc: Shaft - Mild steel, zinc plated, Hasp - Stainless steel 316
- IP65 rated
- 90° left & right stopper
- Suits padlock up to 10mm

ESELON SWING HANDLE, PADLOCKABLE (ALT)

PART NO. (Refer to table)
BOX QTY: 40



- Zinc: Shaft - Mild steel, zinc plated, Hasp - Stainless steel 316
- Stainless: Shaft & hasp - Stainless steel 316
- IP65 rated
- 90° left & right stopper
- Suits padlock up to 13mm

BASE	HANDLE	PART NUMBER
Black EDP coated	Black EDP coated	1107SBB04N
Black EDP coated	Chrome plated	1107SBC04N
Chrome plated	Chrome plated	1107SCC04N
Stainless steel 316	Stainless steel 316	1107SSS04N

ESELON SWING HANDLE, ECONOMY BARREL

PART NO. (Refer to table)
BOX QTY: 40



- Shaft: Mild steel, zinc plated
- IP65 rated
- 90° left & right stopper

BASE / HANDLE FINISH	KEYED	PART NUMBER
Black EDP coated	CL001	1107SBBU3N-01
	92268	1107SBBU3N-02
	CL003	1107SBBU3N-03
Black EDP coated (B) / Chrome plated (H)	CL001	1107SBCU3N-01
	92268	1107SBCU3N-02
	CL003	1107SBCU3N-03
Chrome plated	CL001	1107SCCU3N-01
	92268	1107SCCU3N-02
	CL003	1107SCCU3N-03

HALF EURO PROFILE CYLINDER

PART NO. 1109-SX#
BOX QTY: Sold individually



- 40mm cylinder suits most handles
- Available in a range of key codes

*Please note: Selectlok reserves the right to alter designs and dimensions without notice. © 2024 Selectlok Australia Pty Ltd

SWING HANDLES

MILLENNIUM SWING HANDLE, EURO PROFILE

PART NO. (Refer to table)
BOX QTY: 40

- ▶ Shaft: Mild steel, zinc plated
- ▶ IP65 rated
- ▶ 90° left & right stopper
- ▶ Suits 40mm profile cylinders



BASE / HANDLE FINISH	PART NUMBER
Black EDP coated	1107SBBU3
Black EDP coated / Chrome plated	1107SBCU3
Chrome plated	1107SCCU3

MILLENNIUM SWING HANDLE, EURO PROFILE -
HIGH SECURITY / SUITS 45MM CYLINDER

ZINC, CHROME PART NO. 1107SCCU3-45
STAINLESS STEEL PART NO. 1107SSSU3-45
BOX QTY: 40

- ▶ Material: Mild steel, zinc chrome plated or stainless steel 316
- ▶ IP65 rated
- ▶ 90° left & right stopper
- ▶ Suits 45mm profile cylinders



IND-C SWING HANDLE, AUSTRALIAN OVAL PROFILE

PART NO. 1107SCCA3-IND-C
BOX QTY: 40

- ▶ Vandal resistant
- ▶ Mild steel, zinc plated
- ▶ 90° left & right stopper
- ▶ IP65 rated
- ▶ Semi flush
- ▶ Suits Australian Oval profile cylinders



ESELON SWING HANDLE, EURO PROFILE

PART NO. (Refer to table)
BOX QTY: 40

- ▶ Shaft: Mild steel, zinc plated
- ▶ IP65 rated
- ▶ 90° left & right stopper
- ▶ Suits 40mm profile cylinders



BASE / HANDLE FINISH	PART NUMBER
Black EDP coated	1107SBBU3N
Black EDP coated / Chrome plated	1107SBCU3N
Chrome plated	1107SCCU3N

SWITCH UP

F-SERIES SYMMETRICAL SWING HANDLE

POLYAMIDE, BLACK: HANDLE PART NO. 1107FPPU0
ZINC, BLACK PC: HANDLE PART NO. 1107FBBU0
ZINC, CHROME PLT: HANDLE PART NO. 1107FCCU0

- ▶ Easily ‘SwitchUp’ between padlockable, economy keyed options or half-euro profile inserts (***sold separately***)
- ▶ Unique F-Series modular design allows for easy conversion between patented F-Series cutout & standard Seletrix cutouts (Eselon & Millennium series) via the adapter plate
- ▶ Polyamide: IP42 rated - indoor applications only
- ▶ Zinc, PC/PLT: IP66 rated - full exposure applications
- ▶ 90° handle rotation feedback with “click”
- ▶ Short cam shaft design
- ▶ Symmetrical F-series cutout & 180° handle rotation: ensures compatibility with both RH & LH applications on symmetrically designed doors



CAMS AND MULTI-POINT LOCKING



8MM LOCKING RODS
BOX QTY: 50
(Can be purchased individually)

MATERIAL	AVAIL. SIZES	ROLLER	PART NO.
Mild Steel	600mm ~ 1200mm	No	ROD###E
Mild Steel	600mm ~ 1200mm	Yes	ROD###R
SS-304	600mm ~ 1200mm	Yes	ROD###RSS



ROD SLAM CATCH
PART NO. 2-563

▶ Suits 8mm ~ 10mm round rods
▶ Zinc die-cast, zinc plated



NYLON CONNECT CLIP (FOR 8MM RODS)
PART NO. RG008



ROD ADAPTER (FOR 8MM RODS)
PART NO. RODADAPT

▶ Available in mild steel and stainless steel 304



ROLLER ATTACHMENT (FOR 8MM RODS)
PART NO. RG007

▶ Zinc die-cast, chrome plated and polyamide

POLYAMIDE ROD GUIDES (FOR 8MM LOCKING RODS)
PART NO. (Refer to table)



DOOR RETURN HEIGHT	PART NO.
20mm (A) x 32mm (h)	P3355-02
26mm (A) x 38mm (h)	P3355-01
28mm (A) x 40mm (h)	200-3626.51-00000

CAMS AND MULTI-POINT LOCKING

ADJUSTABLE CAMS

PART NO. (Refer to table)

- Suits SQ 8mm shaft
- Single: 79mm (L), 3-Point: 69mm (L)



TYPE	MATERIAL	PART NUMBER
Single	Zinc Die-Cast, Zinc Plated	1000-1586
3-Point w/o Adapters	Mild Steel, Zinc Plated OR SS-304	1000-1588
3-Point w/ Adapters	Mild Steel, Zinc Plated OR SS-304	1000-1587
3-Point Roller w/ Adapters	Cam: Zinc Die-Cast Adapter: Mild Steel Both: Zinc Plated Roller: Polyamide	1000-1587-RR



FIXED OFFSET (H=) CAMS

PART NO. (Refer to table)

- With or without stopper
- Stainless and 3-point avail. on request
- 45mm (L), other lengths avail. on request

OFFSET (H=) *FLAT = 18mm	STOPPER	PART NO.
2mm ~ 55mm (Contact Us)	Yes	MCAM-##
4mm ~ 40mm (Contact Us)	No	XCAM-##
Single Point	No	100-9755

HEAVY-DUTY GAS STRUTS



GAS STRUTS

BOX QTY: 50 (Can be purchased individually)

Our high-quality gas struts are available in extended lengths from 195mm to 920mm that provide mechanical assistance for lifting and supporting various trailer components.

- Available in different shaft widths, based roughly on extended length
- Various pressures to match the weight requirements of your strut
- Plastic quick-fit ends on 6mm and 8mm shafts (Steel ends available), steel ends on 10mm and 12mm shafts (additional strut ends and brackets available - sold separately)
- QPP Coating on shaft increases protection from corrosion, chipping or dust

EXT. LENGTH	SHAFT WIDTH	PRESSURE
195mm ~ 900mm	6mm 8mm 10mm 12mm	Up to 1700 newtons (N)

D-PULL HANDLES



D-PULL HANDLE

PART NO. (Refer to table)

- Suitable for outdoor applications
- Shaft diameter: 8mm
- Available in brass or mild steel (chrome plated) or stainless steel 304 (polished finish)

WIDTH	MILD STEEL PART NO.	BRASS PART NO.	STAINLESS STEEL 304 PART NO.
76mm	MT203-3M	MT203-3	MT203-3S
102mm	MT206-4M	MT206-4	MT206-4S
152mm	MT206-6M	MT206-6	MT206-6S

O-RINGS, LOCATING PINS AND THUMBSCREWS



RUBBER O-RING
(TO SUIT M6 x 40MM)
PART NO. O-RING#201

RUBBER O-RING
(TO SUIT M8 x 40MM)
PART NO. O-RING#202




LOCATING PIN (M6 x 50mm)
PART NO. LOCATING PIN

- Mild steel, nickel chrome plated

*Please note: Selectlok reserves the right to alter designs and dimensions without notice. © 2024 Selectlok Australia Pty Ltd

O-RINGS, LOCATING PINS AND THUMBSCREWS



THUMBSCREWS
PART NO. (Refer to table)


- ▶ Knurled head
- ▶ 2 x 2mm screw driver slot
- ▶ Mild steel, nickel chrome plated

QUARTER TURNS, L&T HANDLES



SPRING LOADED QUARTER TURN
PART NO. (Refer to table)

- ▶ Housing & insert: Zinc die, chrome plated
- ▶ Multiple drive options available
- ▶ Cam ordered separately
- ▶ IP65 rated
- ▶ Matching quarter turn keys available (Zinc die, Zinc plated)



DRIVE STYLES	PART NO.	QTR. TURN KEYS
7mm square	SQ118-7-32	SQ-7-KEY
8mm square	SQ118-8-32	SQ-8-KEY
8mm square slotted	SQ118-8S-32	N/A
7mm triangle	TL118-7-32	TL-7-KEY
8mm triangle	TL118-8-32	TL-8-KEY
2x4 slotted	SL118-32	N/A
3mm double bit	CL118-3-32	CL-3-KEY
5mm double bit	CL118-5-32	CL-5-KEY



LOCKABLE T-HANDLE (REAR FIXING)
PART NO. (Refer to table)

- ▶ Handle & housing: Zinc die, chrome plated
- ▶ Shaft: Mild steel, zinc plated
- ▶ 90° or 180° rotation, LH or RH application

KEY	PART NO.
92268	ABTU02B
CL001	ABTU01B
CL003	ABTU07B



LOCKABLE T-HANDLE QUARTER TURN
PART NO. (Refer to table)

- ▶ Handle & housing: Zinc die, chrome plated
- ▶ 90° rotation, LH or RH application, IP65

KEY	PART NO.
92268	M110-1-1-92268-00
CL001	M110-1-1-CL001-00



KEY LOCKABLE QUARTER TURN (IP65)
PART NO. (Refer to table)

- ▶ Housing & insert: Zinc die, chrome plated
- ▶ Cam ordered separately
- ▶ Other keys available: 604, 144, CL003

DRIVE STYLES	PART NO.
92268	M0063-1-1-92268-00-1
1333	M063-1-1-05-00-1
CL001	M063-1-1-CL001-00-1



PADLOCKABLE L-HANDLE
HANDLE PART NO. ABLU06B
BRACKET PART NO. (Refer to table)

- ▶ Handle & housing: Zinc die, chrome plated
- ▶ Shaft: Mild steel, zinc plated
- ▶ 90° or 180° rotation, LH or RH application
- ▶ Rear fixing (bracket sold separately)

MATERIAL	LH PART NO.	RH PART NO.
Mild steel	PI5151-03	PI5151-03-1



LOCKABLE L-HANDLE (REAR FIXING)
PART NO. (Refer to table)

- ▶ Handle & housing: Zinc die, chrome plated
- ▶ Shaft: Mild steel, zinc plated
- ▶ 90° or 180° rotation, LH or RH application

KEY	PART NO.
92268	ABLU02B
CL001	ABLU01B
CL003	ABLU07B



LOCKABLE L-HANDLE QUARTER TURN
PART NO. (Refer to table)

- ▶ Handle & housing: Zinc die, chrome plated
- ▶ 90° rotation, LH or RH application, IP65

KEY	PART NO.
92268	M111-1-1-92268-00
CL001	M111-1-1-CL001-00

DOOR COVER STAYS



HEAVY-DUTY COVER STAY
PART NO. (Refer to table)

- ▶ Automatic lock to keep door open
- ▶ For heavy duty applications
- ▶ Extra Heavy Duty options also available

MATERIAL	FINISH	PART NUMBER	BOX QTY
Mild steel	Zinc plated	M179-44-002	50
Stainless steel 304	-	M179-44-001	50

OPENING ANGLE	DIMENSIONS		MINIMAL DOOR WIDTH
	X	Y	
90°	140mm	180mm	403mm
105°	120mm	166mm	389mm
120°	110mm	150mm	373mm
145°	100mm	146mm	369mm



EXTRA HEAVY-DUTY COVER STAY
PART NO. Y230-9306

- ▶ Length: 215mm
- ▶ For extra heavy duty applications
- ▶ Automatic lock to keep door open

- ▶ Suitable for left or right hand applications
- ▶ Material: Mild steel, zinc plated



MILD-DUTY COVER STAY
PART NO. (Refer to table)

- ▶ Length: 292mm
- ▶ Available to suit left or right-hand applications
- ▶ For light to medium duty applications
- ▶ Mild and Extra Heavy Duty options also available

MATERIAL	FINISH	PART NUMBER	HANDEDNESS
Mild steel	Zinc plated	M079-6-3-292-001	Right hand
Mild steel	Zinc plated	M079-6-3-292-002	Left hand
Stainless steel 304	-	M079-4-0-292-002	Left hand

MISCELLANEOUS



BOSS KIT & SHAFT ADAPTER
PART NO. PI5285-KIT-1 (180° rotation)
PART NO. PI5285-KIT (360° rotation)

- ▶ This Boss Kit converts flat rod-capable swing handles into standard flat cam swing handles suitable for round rods.



FLUSH LOCK
PART NO. ALFR02

- ▶ Flush fitting (easy assembly)
- ▶ Multiple key combinations available
- ▶ Economically priced
- ▶ 105.5mm (H) x 71.5mm (W)



SLAM LATCH
PART NO. SEL-229-9001

- ▶ Allows for slam action of doors
- ▶ Can be used with standard handles
- ▶ 124mm (L) x 21mm (W) x 19mm (H)



EMERGENCY INTERNAL HANDLE
PART NO. P2535

- ▶ Fully adjustable
- ▶ Push button action
- ▶ Suits 8mm square shaft
- ▶ Suitable for use with swing handles
- ▶ Multi-point locking compatible

EARTH AND NEUTRAL BARS

IX SERIES EARTH AND NEUTRAL BAR

PART NO. (Refer to table)
BOX QTY: 25



- ▶ 165 amp current rating
- ▶ 2 x domed terminal screws per tunnel
- ▶ 2 x main M8 studs
- ▶ Fixing holes countersunk 4mm clearance
- ▶ Tunnels for 16mm²
- ▶ Numbered to 3mm high
- ▶ Tunnel holes and all edges chamfered
- ▶ RoHS compliant


MOUNTING HOLES:

- ▶ 50mm centres up to 18 pole
- ▶ 120mm centres over 18 pole

NO. OF POLES	MOUNTING HOLES	PART NO.	NO. OF POLES	MOUNTING HOLES	PART NO.
6	50mm	B12006IX	48	120mm	B12048IX
12	50mm	B12012IX	54	120mm	B12054IX
18	50mm	B12018IX	60	120mm	B12060IX
24	120mm	B12024IX	72	120mm	B12072IX
30	120mm	B12030IX	84	120mm	B12084IX
36	120mm	B12036IX	96	120mm	B12096IX
42	120mm	B12042IX	108	120mm	B12108IX

QX SERIES EARTH AND NEUTRAL BAR

PART NO. (Refer to table)
BOX QTY: 25



- ▶ 165 amp current rating
- ▶ 2 x domed terminal screws per tunnel
- ▶ 2 x main M8 studs
- ▶ Fixing holes countersunk 4mm clearance
- ▶ Tunnels for 16mm²
- ▶ Numbered to 3mm high
- ▶ Tunnel holes and all edges chamfered
- ▶ RoHS compliant

MOUNTING HOLES:

- ▶ 50mm centres up to 18 pole
- ▶ 120mm centres over 18 pole

NO. OF POLES	MOUNTING HOLES	PART NO.	NO. OF POLES	MOUNTING HOLES	PART NO.
6	50mm	B12006QX	48	120mm	B12048QX
12	50mm	B12012QX	54	120mm	B12054QX
18	50mm	B12018QX	60	120mm	B12060QX
24	120mm	B12024QX	72	120mm	B12072QX
30	120mm	B12030QX	84	120mm	B12084QX
36	120mm	B12036QX	96	120mm	B12096QX
42	120mm	B12042QX	108	120mm	B12108QX

INSULATORS

INSULATOR (FOR EARTH AND NEUTRAL BARS)

PART NO. BISEL
BOX QTY: 100



- ▶ Made of plastic
- ▶ Compatible with both **IX** or **QX** series earth and neutral bars

INSULATORS



OCTAGONAL STAND-OFF INSULATORS

PART NO. (Refer to table)
BOX QTY: 50

- ▶ Glass reinforced polyester, moulded-in brass insert
- ▶ Octagon shape for easy installation
- ▶ High dielectric and mechanical strength
- ▶ Chemical, Oil, Wear and Corrosion resistant

HEIGHT (MM)	WIDTH (MM)	INSERT	TENSILE STRENGTH	TORQUE	PART NO.
25	22	M6	227kg	1.4kg Mtrs	I025EN-E
30	30	M6	272kg	1.4kg Mtrs	I030EN-E
35	32	M8	295kg	3.5kg Mtrs	I035FN-E
40	41	M8	363kg	3.5kg Mtrs	I040FN-E
45	46	M8	454kg	3.5kg Mtrs	I045FN-E
50	36	M8	409kg	3.5kg Mtrs	I050FN-E
50	46	M10	500kg	6.9kg Mtrs	I050GN-E
60	60	M10	907kg	6.9kg Mtrs	I060GN-E
75	50	M10	680kg	6.9kg Mtrs	I075GN-E
50	46	M12	680kg	11.8kg Mtrs	I050HN-E
75	50	M12	680kg	11.8kg Mtrs	I075HN-E

DIRAK GMBH



DIRAK HEAVY DUTY LATCH SYSTEM FOR HVAC
PART NO. 232-####

- ▶ Multiple handle configurations available
- ▶ Please contact us or refer to Dirak's website for more information

- ▶ IP65 according to DIN EN 60529 by sealing kit (optional)
- ▶ Handle (outside) available both with & without key cylinder or insert
- ▶ Suitable for different door-thicknesses



DIRAK SNAPLINE PINTLE HINGE (DST)
PART NO. 417-9018.00-00019

- ▶ Dirak Snapline D-Snap Technology
- ▶ Lift-off
- ▶ RH and LH application
- ▶ 180° Opening angle



DIRAK FLUSH-MOUNT COMPRESSION LATCH - STAINLESS STEEL 316
PART NO. 148-####.##-#####

- ▶ 6mm compression
- ▶ Available in 28/37mm housings (IP69K)
- ▶ Multiple inserts available



DIRAK LEVELLING FOOT (M6/M8)
PART NO. 580-90##.##-#####

- ▶ Inclination angle of +/- 25°
- ▶ Anti-slip insert included
- ▶ Please contact us or refer to Dirak's website for more information



DIRAK GROUNDING CAGE NUT
PART NO. 203-19##.##-#####

- ▶ Toolless installation from front or rear
- ▶ Suits high-torque/tensile force 3~8Nm
- ▶ Secure joining of metal sheets (with M6 grounding nut)



DIRAK SMALL SQUARE WINDOW
PART NO. 251-9102.00-00000

- ▶ Clip-in: Suits doors 0.8 to 2.5mm thick
- ▶ IP66 with o-ring
- ▶ Polycarbonate PC window, NBR o-ring
- ▶ 110mm (W) x 110mm (L)



DIRAK BRIDGE HANDLE
PART NO. 213-####.##-#####


- ▶ Handle with Ø30mm in various lengths
- ▶ For vertical or horizontal application
- ▶ Please contact us or refer to Dirak's website for more information

Selectlok is the exclusive Australian distributor & stockist of Dirak components (Quality Greman Engineering). Please contact us for Part No's, pricing or availability.

*Please note: Selectlok reserves the right to alter designs and dimensions without notice. © 2024 Selectlok Australia Pty Ltd

RUBBER SEAL AND FOAM TAPES

CLOSED CELL FOAM TAPES
(AVAILABLE IN EITHER EPDM & PVC NITRILE)
PART NO. (Refer to table)
BOX QTY: Varies based on the roll: material, width & thickness



MATERIAL	AVAILABLE WIDTHS	AVAILABLE THICKNESS'	PART NO.
PVC Nitrile	10mm ~ 25mm (A)	3mm ~ 9mm (B)	NITFTAxB
EPDM	9mm ~ 48mm (A)	3mm ~ 12mm (B)	EPDMFTAxB



RUBBER BULL NOSE
PART NO. RSB256
BOX QTY: 50m coil

- ▶ Profile: 25mm x 6mm
- ▶ Subject to availability and/or leadtimes



PVC EDGE PROTECTION MEDIUM PROFILE
PART NO. PACK-10802-07 (7m roll)
PART NO. 1011-10802 (100m roll)
BOX QTY: 7m pack **or** 1 x 100m roll (box)

- ▶ Grip range: 1.0 ~ 2.0mm



RUBBER PINCHWELD - SMALL SIDE MOUNT BUBBLE
PART NO. 1011-10212
BOX QTY: 1 x 100m roll

- ▶ Grip range: 1.0 ~ 2.0mm



RUBBER PINCHWELD - SMALL TOP MOUNT BUBBLE
PART NO. PACK-110-07 (7m roll)
PART NO. 1011-110 (50m roll)
BOX QTY: 7m pack **or** 2 x 50m rolls (box)

- ▶ Grip range: 1.0 ~ 2.0mm



RUBBER PINCHWELD - MEDIUM TOP MOUNT BUBBLE
PART NO. PACK-105-07 (7m roll)
PART NO. 1011-105 (50m roll)
BOX QTY: 7m pack **or** 2 x 50m rolls (box)

- ▶ Grip range: 1.0 ~ 3.0mm



RUBBER PINCHWELD - LARGE SIDE MOUNT BUBBLE
PART NO. 1011-A3297
BOX QTY: 2 x 50m rolls

- ▶ Grip range: 2.0mm



PVC EDGE PROTECTION SMALL PROFILE
PART NO. PACK-10801-07 (7m roll)
PART NO. 1011-10801 (100m roll)
BOX QTY: 7m pack **or** 1 x 100m roll (box)

- ▶ Grip range: 0.8 ~ 1.5mm



PVC EDGE PROTECTION LARGE PROFILE
PART NO. PACK-10803-07 (7m roll)
PART NO. 1011-10803 (100m roll)
BOX QTY: 7m pack **or** 1 x 100m roll (box)

- ▶ Grip range: 1.0 ~ 4.0mm



RUBBER PINCHWELD - SMALL SIDE MOUNT BUBBLE
PART NO. PACK-109-07 (7m roll)
PART NO. 1011-109 (50m roll)
BOX QTY: 7m pack **or** 2 x 50m rolls (box)

- ▶ Grip range: 1.0 ~ 2.0mm



RUBBER PINCHWELD - MEDIUM SIDE MOUNT BUBBLE
PART NO. PACK-106-07 (7m roll)
PART NO. 1011-106 (50m roll)
BOX QTY: 7m pack **or** 2 x 50m rolls (box)

- ▶ Grip range: 1.0 ~ 2.5mm



RUBBER PINCHWELD - MEDIUM TOP MOUNT BUBBLE (FOR CHECKERPLATE)
PART NO. 1011-105-C
BOX QTY: 1 x 100m roll

- ▶ Grip range: 2.5 ~ 3.5mm



SELF-ADHESIVE EPDM RUBBER TOP MOUNT, 3M ADHESIVE
PART NO. 9187STS
BOX QTY: 1 x 50m roll

- ▶ Profile: 16.7mm x 18mm

For more information on price and availability, drawings or technical data please consult your local Selectlok Account Manager, or visit www.selectlok.com.au

IOT SERIES ELECTRONIC SWING HANDLE (IP65)

PART NO. 1107SBBE01-IND-C-001

- ▶ Access method: Mechanical key + remote control (DO)
- ▶ Lock status indicator light (blue/green)
- ▶ IP65 ingress protection rated
- ▶ Includes 3M loose wiring harness
- ▶ RC2 pry proof rated
- ▶ Unlock current $\leq 350\text{mA}$
- ▶ Standby current $\leq 50\text{mA}$
- ▶ Mechanical key lockable with cylinder barrel
- ▶ Keyed alike 001 (Other codes may be available upon request)
- ▶ Cams sold separately

CUTOUT:

- ▶ IND-C

MATERIALS & FINISH:

- ▶ **Housing:** Zinc-die
- ▶ **Handle:** Zinc alloy
- ▶ **Finish:** Textured powder coat, black

REMARKS:

- ▶ Note: The DO unlocking time is recommended to be 20s
- ▶ Open with mechanical key: When the machine is opened, first open the dust cover with the dust cover key, then insert the mechanical key, press down and rotate clockwise to open the handle.
- ▶ Open the IoT Lock with DO remote unlocking: Issue a remote command to unlock the lock, at this time the lock status indicator flashes from blue to green and accompanied by the buzzer sound, at this time, press the PUSH point at the end of the lock handle and the handle will automatically pop up. Rotate the handle to drive the locking mechanism such as a cam or rod control mechanism to complete the opening action.

CENTRAL LOCKING SWING HANDLE

PART NO. 1107-CL-01

- ▶ Electrically actuated
- ▶ Park position with "click"
- ▶ Can be connected to vehicles existing system
- ▶ Key override (lock/unlock)
- ▶ 2 wire connection - 12 volt DC
- ▶ 90° left & right stopper

DIMENSIONS:

- ▶ Shaft Length = 68mm
- ▶ Shaft Square Size = 8mm

MATERIAL & FINISH:

- ▶ Handle & base: Zinc die
- ▶ Finish: Chrome plated
- ▶ Dish: Stainless steel 304
- ▶ Shaft: Mild steel, zinc plated

iLOQ NFC CAM LOCK

PART NO. G50S.1

- ▶ BATTERY-FREE programmable electromechanical cam lock for iLOQ S50 locking system
- ▶ NFC-powered
- ▶ Opening with NFC enabled smartphone* or iLOQ K50S key fob
- ▶ Secured using powerful AES256 encryption and mutual authentication
- ▶ Access right list for access groups, blocklist for individual lost keys
- ▶ Internal audit trail record with time stamp (can be configured on/off)
- ▶ Supports time restrictions



iLOQ NFC DIN HALF-CYLINDER (HALF-EURO)

PART NO. G50S.1

- ▶ BATTERY-FREE programmable electromechanical cam lock for iLOQ S50 locking system
- ▶ NFC-powered
- ▶ Opening with NFC enabled smartphone* or iLOQ K50S key fob
- ▶ Secured using powerful AES256 encryption and mutual authentication
- ▶ Compatible with DIN 18252 Europrofile cylinder standard
- ▶ Access right list for access groups, blocklist for individual lost keys
- ▶ Internal audit trail record with time stamp (can be configured on/off)
- ▶ Supports time restrictions

The patented, award winning iLOQ S50 locking system offers advanced security and convenient access sharing capabilities for master-key locking environments.

Selectlok began as a small family business in the suburbs of Preston, Victoria in 1978. We now call Tullamarine, Victoria our home, with sales representatives across all of Australia servicing our clients needs.

We work directly with manufacturers to create innovative industrial hardware solutions, and are a driving force for creating ingenious solutions specifically for the Australian market.

Our in-house products and distributed ranges use only the highest quality manufacturing processes and materials. That's why we are trusted by the biggest manufacturers in Australia.



HEAD OFFICE | CUSTOMER SERVICE

13 TREVI CRESCENT, TULLAMARINE, VIC 3043

TEL (03) 8318 4900

EMAIL SALES@SELECTLOK.COM.AU



DISCOVER MORE ONLINE

www.selectlok.com.au