

Test Report



MATERIAL PROPERTIES REPORT

Edge Protection Sealing Profiles

Sample Material:	EPDM - Solid Rubber, EPDM - Sponge Rubber
Part Number:	1011-106
Report Job No#:	A1 549
Test Period:	24/11/2014
Test Standards:	
Edge Protector	DIN ISO 3302-1 E2
Sealing	DIN ISO 3302-1 E3
Lengths	DIN ISO 3302-1 L3
Approved by:	LOK Technical Product Manager LOK QC Manager

RESULTS SUMMARY

Hardness:	
Edge Protector	65 +/- 5 Shore A
Sealing Density	0.6 +/- 0.1 g/cm ³
Colour:	Black
Metal Carrier:	26 x 0.75 (Wire Carrier)
Operation Temperature:	-40°C to +100°C
UV Stability:	Good
Stable Against:	Alcohol, Ozone, Climate Resistance, Lyes & Low Acids, Acetone
Unstable Against:	CKW, Concentrated Acids, Aromatic Hydrocarbons, Oil & Petrol

*** END OF REPORT ***

Disclaimer: The above document is derived from original test reports and certificates carried out by the manufacturer and/or independent lab facilities. The contents of this report are meant for information purposes only relating to product & material quality, industry standards and/or guidelines. The contents of this report should not be used for advertisement, evidence or litigation purposes.