

## Test Report



### MATERIAL PROPERTIES REPORT

#### Edge Protection Sealing Profiles

**Sample Material:** EPDM - Solid Rubber, EPDM - Sponge Rubber  
**Part Number:** 1011-105

**Report Job No#:** A2 513  
**Test Period:** 01/09/2008

**Test Standards:**  
Edge Protector DIN ISO 3302-1 E2  
Sealing DIN ISO 3302-1 E3  
Lengths DIN ISO 3302-1 L3

**Approved by:** LOK Technical Product Manager  
LOK QC Manager

#### RESULTS SUMMARY

**Hardness:**  
Edge Protector 60 +/- 5 Shore A  
Sealing Density 0.6 +/- 0.1 g/cm<sup>3</sup>

**Colour:** Black

**Metal Carrier:** 26 x 0.75 (Wire Carrier)

**Operation Temperature:** -40°C to +100°C

**UV Stability:** Good

**Stable Against:** Alcohol, Ozone, Climate Resistance, Lyes & Low Acids, Acetone

**Unstable Against:** CKW, Concentrated Acids, Aromatic Hydrocarbons, Oil & Petrol

\*\*\* END OF REPORT \*\*\*

Disclaimer: The above document is derived from original test reports and certificates carried out by the manufacturer and/or independent lab facilities. The contents of this report are meant for information purposes only relating to product & material quality, industry standards and/or guidelines. The contents of this report should not be used for advertisement, evidence or litigation purposes.