

TECHNICAL DATASHEET

M099 SERIES

50x50 Screw-On Hinge (SOH)

Industrial Butt Hinge

Features

- Industrial butt hinge, screw-on design (SOH)
- · Engineered for use with flush mounted doors
- · Suitable for outdoor applications
- 270 ° rotation
- · Mounting:
 - Rear fixing M6 x 11mm studs
 - Front fixing Ø 6.6mm countersunk holes
 - Combination front + rear fixing: Availability on request (MOQ's & ext. leadtimes may apply)



· Hinge: Zinc, die-cast Pin: Stainless steel

Finish: black, EDP coated OR chrome plated

· Maximum load capacity:

Axial load - Tested to 5,044N force

Radial load - Tested to 7,192N force

Note: 10N (newtons) is equivilent to 1kg (kilograms) of force / pressure



Part Number	Mounting	Dimensions (mm)	Finish	Maximum Load Capacity (N)
M099-1-2-1	M6 Studs x 11mm (L) / Rear Fixing	50 (L) x 50 (W) x 15 (H)	Black, EDPC	Axial - 5,044N / Radial - 7,192N
M099-1-2-2	M6 Studs & Ø 6.6mm Holes / Combo Fixing	50 (L) x 50 (W) x 15 (H)	Black, EDPC	Axial - 5,044N / Radial - 7,192N
M099-1-2-4	Ø 6.6mm Countersunk Holes / Front Fixing	50 (L) x 50 (W) x 15 (H)	Black, EDPC	Axial - 5,044N / Radial - 7,192N

