

L101 SERIES

Flush Pull Ring Latch

Stainless Steel

Features

- Stainless steel
- Emergency internal actuation (regardless of whether in locked or unlocked position)
- Single, round-hole installation
- Locking and non-locking available
- **Mounting:** Rear fixing, M5 x 20mm Phillips pan-head screws
- **Grip range:** ≤ 25.5mm
- **Material thickness range:** 7mm ~ 12mm
- **Max. working load:** 835 N (187 lbf)
- **Max. tightening torque (mounting screws):** 1.7 Nm (15 in.lbf)




Materials & Finish

- **Material:** Stainless steel 316
- **Finish:** Electropolished
- **Round cutout:** Ø50 mm

Remarks

- Other grip ranges and materials/finishes available (Subject to MOQ's and lead-times)



Part Number	Description	Key Code	Material Thickness	Grip Range	Internal Release	Material & Finish
L101-01-KEY	2x Replacement Keys	#4	1.5mm	N/A	N/A	Polished SS-316
L101-01-SS-7	Key Lockable Latch	#4	7 ~ 12 mm	≤ 25.5mm	Yes	Polished SS-316
L101-02-SS-7	Non-Locking Latch	N/A	7 ~ 12 mm	≤ 25.5mm	Yes	Polished SS-316

Technical Drawings

