

MIDNIGHT V2

2 Wires Central Locking Actuator Kit

Features

- Push/pull force: > 5.0 kgs
- Ultrasonic welding and fastened with rivets, water resistant
- 360° swivel head/fixed head available
- Input voltage: 12v / 24v available
- Working temperature range: - 40°C ~ + 80°C
- Amp draw: 4 ~ 4.5 amp per load (Selectlok recommends no more than 3 x units per 40 amp relay)
- Kit is suitable only for Midnight V2 range

Materials & Finish

- Actuator housing: ABS, black
- Mounting plate: Mild steel, zinc plated
- Protective cover: Mild steel, zinc plated
- Connecting link & limit sleeve: Mild steel, zinc plated
- Pan head M4x16 screw & washers: Mild steel, zinc plated
- M4 hex nut: Stainless steel 304

Measurements

Actuators

- Dimensions: 140mm (L) x 63mm (H) x 31mm (W)
- Push/pull throw: 16.5mm
- Mounting holes & spacing: 57.5mm x ø 4mm

Mounting plate & cover

- Mounting plate: 210mm (L) x *180mm x 2mm (H)
- *W1: 80mm, *W2: 100mm
- Protective cover: 180mm (L) x 72.5mm (W) x 36.5mm (H)



Part Number	Push/Pull Force	Push/Pull Throw	Voltage	Amp Draw	Head Type
10503-CL-L	> 5 kg	16.5 mm	12 V	4 ~ 4.5 amp per load	Swivel
10503-CL-L-24v	> 5 kg	16.5 mm	24 V	4 ~ 4.5 amp per load	Swivel
10503-CL-R	> 5 kg	16.5 mm	12 V	4 ~ 4.5 amp per load	Swivel
10503-CL-R-24v	> 5 kg	16.5 mm	24 V	4 ~ 4.5 amp per load	Swivel

MIDNIGHT V2

2 Wires Central Locking Actuator Kit

